

1

DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

AD-A217 077

1 to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and
tion of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including
vices, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302,
Project (0704-0188), Washington, DC 20503.

2. REPORT DATE

December 1989

3. REPORT TYPE AND DATES COVERED

paper/presentation

4. TITLE AND SUBTITLE

ECHOLOCATION SIGNALS OF ODONTOCETES IN OPEN WATERS

6. AUTHOR(S)

W. W. L. Au

5. FUNDING NUMBERS

PE: 0602435N
PN: MMB2
WU: DN688 674

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)

Naval Ocean Systems Center
San Diego, CA 92152-5000

Accession For

NTIS CRA&I
DTIC TAB

Unannounced
Justification

By

Distribution

Availability Codes

Dist

Avail and/or
Special

A-1 21

8. PERFORMING ORGANIZATION
REPORT NUMBER

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)

Naval Ocean Systems Center
Block Programs
San Diego, CA 92152-5000

10. SPONSORING/MONITORING
AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY STATEMENT

Approved for public release; distribution is unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

The characteristics of echolocation signals used by the Atlantic bottlenose dolphin (*Tursiops truncatus*) and by the beluga or white whale (*Delphinapterus leucas*) in target detection and discrimination experiments in open waters will be discussed. Echolocation signals measured in open waters have been found to have considerably different properties than those measured in tanks. The primary reason for the differences in echolocation signals may be attributed to the use of very-low-intensity signals by animals in tanks and the use of higher-intensity (> 40 dB) signals in open waters. Signals are projected in the forward direction along a narrow beam and echoes are detected by a receiving beam that overlaps the transmission beam. Acoustic properties of these signals, such as source sound-pressure levels, signal waveform, frequency spectrum, peak frequency, bandwidth, and click intervals, will be considered. The acoustic characteristics of echolocation signals propagating from the animal's head will also be discussed. The structure of the acoustic field directly forward of the animal, the transition region between the near and far acoustic fields, the directivity patterns in the vertical and horizontal planes, and off-axis distortion of signals will be addressed.

DTIC
ELECTE
JAN 11 1990
S D

Published in the *Journal Acoustic Society of America*, Suppl. 1, Vol. 86, Fall, 1989.

14. SUBJECT TERMS

marine biosystems; marine biology; biological noise; DTIC TAB

15. NUMBER OF PAGES

16. PRICE CODE

17. SECURITY CLASSIFICATION
OF REPORT

UNCLASSIFIED

18. SECURITY CLASSIFICATION
OF THIS PAGE

UNCLASSIFIED

19. SECURITY CLASSIFICATION
OF ABSTRACT

UNCLASSIFIED

20. LIMITATION OF ABSTRACT

UNLIMITED